RELY ON EXCELLENCE

MagBlower model 283

Blowers

Features

- Hermetically sealed
- No contamination of process
- No process gas to atmosphere
- Always below 85 dBA noise levels
- Low heat generation and high torque transfer magnetic coupling
- Pulsation free gas flow
- Engineered designs available to meet special requirements

Functional description

The Magnetic coupling allows power transfer from the electric motor to the impeller without mechanical contact; eliminating the need for a shaft seal. The bearings suitable for the application support the impeller shaft in the blower housing. The gas enters the blower and the energy put into the gas from the blower impeller, produces flow and a pressure increase as required for the application before exiting the blower outlet.

Notes

Options:

- Horizontal or vertical design
- Centrifugal or regenerative impeller

Advantages

- The MagBlower delivers abundant, reliable, and consistent gas flow, in every situation with no leakage.
- Simple to set-up, easy to operate
- High reliability and availability
- Designed for continuous operation
- Low maintenance costs
- Energy efficient

Operating range

Pressure: Vacuum ... 4 bar (30 PSI)
Temperature:
-40 °C ... +200 °C (-40 °F ... +392 °F)
Head: ... 260 Kpa (38 PSI) on air
Flow: 475 m3/h (280 CFM) on air

Models outside of these operating ranges are available on request.

Recommended applications

- Oil and gas industry
- Refining technology
- Chemical industry
- Petrochemical industry
- Pharmaceutical industry
- Nuclear applications
- Research
- Manufacturing
- Vapor recovery

eagleburgmann.com
info@eagleburgmann.com

All technical specifications are based on extensive tests and our many years of experience. The diversity of possible applications means, however, that they can serve only as guide values.
We must be notified of the exact conditions of application before we can provide any guarantee for a specific case. Subject to change.

- Single to four stage in series or parallel
- Bearings to meet application requirements
- Noise reduction cover



Item	Description
1	Motor
2	Magnetic coupling
3	Bearing assembly
4	Blower housing
5	Impeller
6	Inlet
7	Outlet

All technical specifications are based on extensive tests and our many years of experience. The diversity of possible applications means, however, that they can serve only as guide values.
We must be notified of the exact conditions of application before we can provide any guarantee for a specific case. Subject to change.

Product variants



Blower type: Four-stage, regenerative aerofoil
Speed: min. 3,600 min^{-1}, max. 6,000 min^{-1}
Design pressure: Vacuum to 4 barg (58 PSIG)
Design temperature: 150 °C (300 °F)
Motor size:
230/460 V, 3 phase, 60 Hz, 56 kW (75 hp)
Size: height 171 cm (67.4"), diameter 70 cm (27.5"),
inlet-to-outlet distance 101 cm (39.7")
Weight: approx. 1,800 kg (4,000 lb)

Charts



Performance curves for type 283-0100

All technical specifications are based on extensive tests and our many years of experience. The diversity of possible applications means, however, that they can serve only as guide values.
We must be notified of the exact conditions of application before we can provide any guarantee for a specific case. Subject to change.