

RELY ON EXCELLENCE

## Camprofile serrated gasket 9588

Packings & Gaskets | Metallic gasket



### Features

The serrated gasket 9588 has a concentrically-machined profile based on a 4 mm thick stainless steel base plate. This is coated on both sides with a 0.5 mm thick layer of pure graphite (purity > 98%). Thicker layers are available on request. The serrated gasket 9588 is easy to handle and is particularly suitable for applications in the chemical and petrochemical industries and in power station technology.

### Notes

After the initial warm-up, we recommend retightening the bolts (with the system depressurized) in order to compensate for any minor settling of the overlay material and thus maintain optimum surface pressure. If the gasket is replaced, the undamaged serrated profile ring can be reused.

### Advantages

- Maximum compressive strength
- Low minimum surface pressure required
- High temperature stability
- Ideal for withstanding temperature/pressure cycling

### Operating range

Pressure:  $p = 400$  bar  
Higher pressures available on request  
Temperature

- Continuous operation:  
 $t = -200$  °C ...  $+550$  °C

Recommended surface roughness:  
 $Rz = 12.5$  ...  $50$   $\mu\text{m}$

Chemical resistance:  $\text{pH} = 0$  ...  $14$

### Materials

- Serrated ring: Standard 1.4541 and 1.4571
- Gasket overlay: Statotherm pure graphite, purity > 98%

### Standards and approvals

- TA-Luft
- Fire-Safe (API 607)

### Recommended applications

Industries

- Process industry
- Oil & gas industry
- Petrochemical industry
- Chemical industry
- Power plant technology
- Building services engineering

Mechanical units

- Heat exchangers
- Covers
- Tank hatches
- Process boilers
- Flanged connections
- Pipe connections
- Furnaces
- Maintenance seal