

RELY ON EXCELLENCE

Thermoflon 6230

Packings & Gaskets | Packing for pumps



Features

Thermoflon 6230 is a diagonally braided packing made from 100% genuine GFO (graphite incorporated PTFE yarn). With its universal structure, the packing is used in almost every branch of industry.

Notes

For sealing hot water pumps, the required leakage must always emerge in liquid form in order to lubricate the packing. The compression packing will have to be cooled via a lantern ring or a jacket, gland or shaft cooling system if the heat radiation via the stuffing box housing is not sufficient.

Advantages

- Treats shafts gently
- High cross-sectional stability
- Highly flexible
- Outstanding functional efficiency
- Very good emergency running properties
- Very high thermal conductivity
- No embrittlement
- Does not age
- Long service life

Operating range

Pumps

Pressure: p = 25 bar

Sliding velocity: vg = 25 m/s

Valves Pressure: p = 100 bar

Sliding velocity: vg = 2 m/s

Plunger Pumps

Pressure: p = 250 bar

Sliding velocity: vg = 2 m/s

Mixers, agitators, kneaders, filters

Pressure: p = 25 bar

Sliding velocity: vg = 2 m/s

Temperature

- Continuous operation:
t = -200 °C ... +280 °C
- Hot water:
without cooling... +140 °C

Chemical resistance:

pH = 0 ... 14

Not suitable for use in oxidizing media such as oleum (fuming nitric acid), gaseous fluorine and molten alkali metals.

Recommended applications

Industries

- Process industry
- Oil and gas industry
- Petrochemical industry
- Chemical industry
- Pharmaceutical industry
- Power plant technology
- Pulp and paper industry
- Water and waste water technology
- Mining industry
- Building services industry
- Food and beverage industry
- Shipbuilding
- Sugar industry
- Metal production and processing

Mechanical units

- Pumps
- Agitators
- Mixers
- Kneaders