EagleBurgmann
a member of EKK and FREUDENBERG

RELY ON EXCELLENCE

Burajet 8032/HHP Injection Device

Packings & Gaskets | Tools Maintenance products

Advantages

- Easy to handle
- Can be used multiple times on different machines
- Greater distance from the machine is possible

Operating range

For supplying and topping up Burajet fiber injectable compound

Materials

It consists of the following components:

- Hydraulic cylinder with hand lever
- Nipple for lantern ring/flush water connection
- Stop valve
- Pressure hose with pressure gauge

Features

The Burajet injection gun 8032/ HHP is a hydraulic gun for fiber-injectable packings allowing easy injection of the compound into the stuffing box space. An injection gun can be used for multiple applications or machines.

Notes

The packing can be installed by hand while the equipment is stopped with the gland follower open. With the gland plate closed and while the equipment is stopped, the packing can be injected for the first time using the hydraulic injection gun 8032/HHP via the flush water/ lantern ring connection. If there is no connection, it may be attached later.

The packing can be installed by hand while the equipment is stopped with the gland follower open. With the gland plate closed and while the equipment is stopped, the packing can be injected for the first time using the hydraulic injection gun 8032/HHP via the flush water/ lantern ring connection. If there is no connection, it may be attached later.

Conversion

Conversion to the fiber compound packing is problem-free and requires little technical

eagleburgmann.com
info@eagleburgmann.com

All technical specifications are based on extensive tests and our many years of experience. The diversity of possible applications means, however, that they can serve only as guide values.
We must be notified of the exact conditions of application before we can provide any guarantee for a specific case. Subject to change.

equipment. Use the packing extractor 9611 to remove the old packing. Then retain the injectable fiber packings between two braided packing rings.

All technical specifications are based on extensive tests and our many years of experience. The diversity of possible applications means, however, that they can serve only as guide values.
We must be notified of the exact conditions of application before we can provide any guarantee for a specific case. Subject to change.