



Marine & Offshore

Certificate number: 55048/B0 BV File number: ACM 153/1013/2 Product code: 1532H

This certificate is not valid when presented without the full attached schedule composed of 7 sections

www.veristar.com

TYPE APPROVAL CERTIFICATE

This certificate is issued to EagleBurgmann Espey GmbH Moers - GERMANY

for the type of product WATERTIGHT SHAFT BULKHEAD PENETRATION DEVICES BULKHEAD SHAFT SEAL ESPEY WDK-BHS

Requirements:

BUREAU VERITAS Rules for the Classification of Steel Ships

This certificate is issued to attest that Bureau Veritas Marine & Offshore did undertake the relevant approval procedures for the product identified above which was found to comply with the relevant requirements mentioned above.

This certificate will expire on: 04 Dec 2028

For Bureau Veritas Marine & Offshore, At BV HAMBURG, on 04 Dec 2023, Heiko Lange

This certificate was created electronically and is valid without signature



This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with Bureau Veritas Marine & Offshore. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. This certificate is issued within the scope of the General Conditions of Bureau Veritas Marine & Offshore available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas Marine & Offshore for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

The electronic version is available at: http://www.veristarnb.com/veristarnb/jsp/viewPublicPdfTypec.jsp?id=x35quefv2e BV Mod. Ad.E 530 June 2017 This certificate consists of 3 page(s)

THE SCHEDULE OF APPROVAL

<u>1. PRODUCT DESCRIPTION:</u>

Bulkhead shaft seals Espey WDK-BHS

Shaft diameter 100 mm up to 350 mm

1.1 Design:

Watertight bulkhead shaft seals, basically composed of a housing in two parts and multi-part seal rings with tension springs and detent. The bulkhead seals are used for shaft diameters from 100 mm up to 350 mm.

Shaft diameter [mm]	Max. shaft speed [min-1]	Max. effective pressure [bar]	Max. temperature [°C]
100	7643		
110	6945		
120	6366		
130	5876		
140	5457		
150	5093		
160	4775		
170	4494		
180	4244		
190	4021		
200	3820		
210	3638		
220	3472	3	225
230	3321		
240	3183		
250	3056		
260	2938		
270	2829]	
280	2728		
290	2634		
300	2546		
310	2464		
320	2388		
330	2315		
340	2247		
350	2184		

1.3 Material:

Housing	Stainless Steel (1.4571)
Sealing ring	Carbon-PTFE-Compound
Tension spring	1.4571
Detente	1.4571

2. DOCUMENTS AND DRAWINGS:

2.1 Documents:

- Eagle Burgmann Catalogue Carbon Floating Ring Seals, Ref.: EPCE/E2/1.000/08.12/9.7.1 ©Eagle Burgmann Espey, Germany.

- Technical Info Bulkhead Seal Espey WDK-BHS

2.2 Drawing:

Designation	Drawing no.	Rev.
Bulkheadseal	ESPEY-WDK-BHS	01

3. TEST REPORTS:

- 3.1 Leakage test on Espey WDK-BHS diameter 100 mm, Report no. HN2294452.
- 3.2 Leakage test on Espey WDK-BHS diameter 320 mm, Report no. HN2316164.

4. APPLICATION / LIMITATION:

- 4.1 The bulkhead shaft seals are intended to be used exclusively to seal rotating ship shafts against bulkheads to avoid a flooding of related compartments in case of accidents.
- 4.2 The used materials have to be suitable for the intended services.
- 4.3 The bulkhead seals will be fitted according to the BUREAU VERITAS Rules requirements and the manufacturer's instructions.
- 4.4 Where the bulkhead is required to have specific fire integrity characteristics, arrangements are to be made to maintain the fire integrity of the bulkhead in way of penetration.

5. PRODUCTION SURVEY REQUIREMENTS:

- 5.1 The bulkhead seals are to be supplied by **EagleBurgmann Espey GmbH** in compliance with the type described in this certificate.
- 5.2 This type of product is within the category HBV of BUREAU VERITAS Rule Note NR320 and as such does not require a BUREAU VERITAS product certificate.
- 5.3 **EagleBurgmann Espey GmbH** has to make the necessary arrangements to have its works recognised by BUREAU VERITAS in compliance with the requirements of NR320 for HBV products.
- 5.4 For information, **EagleBurgmann Espey GmbH** has declared to BUREAU VERITAS the following production site: **EagleBurgmann Espey GmbH**, **Moers / GERMANY**

6. MARKING OF PRODUCT:

Each bulkhead seal is to be clearly marked with at least:

- Size
- Serial number

<u>7. OTHERS:</u>

- 7.1 It is **EagleBurgmann Espey GmbH**'s responsibility to inform shipbuilders or their sub-contractors of the proper methods of fitting, use and general maintenance of the approved equipment and the conditions of this approval.
- 7.2 This certificate supersedes the Type Approval Certificate N° 55048/A0 BV issued on 22 Nov 2018 by the Society.

*** END OF CERTIFICATE ***